

## 4300 Pressure Limiting Valve

- ✓ High precision
- ✓ Compact size
- ✓ Easy to install
- ✓ Automatic reset
- ✓ Robust
- ✓ Excellent
- ✓ Very low pressure ranges available
- ✓ Extensive ranges
- ✓ Non-venting design
- ✓ Suitable for use with oxygen (optional)
- ✓ Adjustable shut of pressure



Tradinco Instruments distributes, designs, manufactures and repairs calibration and sensing equipment and instruments for various industries.

Our core values are quality, service and keeping our knowledge up to date with the latest technical innovations, to find the best solutions for our customers.

# 4300 Pressure Limiting Valve

---

## TECHNICAL SPECIFICATIONS

### Range

0 - 0.1 bar  
0 - 0.7 bar  
0 - 1 bar  
0 - 2 bar  
0 - 4 bar  
0 - 7 bar  
0 - 10 bar

**Max. inlet pressure: 17 bar**

### Pitch 0.5 mm

3005 - 2P  
3005 - 10P  
3005 - 1B  
3005 - 30P  
3005 - 60P  
3005 - 100P  
3005 - 10B

### Pitch 1.0 mm

3010 - 2P  
3010 - 10P  
3010 - 1B  
3010 - 30P  
3010 - 60P  
3010 - 100P  
3010 - 10B

Material of construction  
steel

Body: aluminium alloy, Trim: stainless steel, brass, cadmium plated

Connections

Diaphragms: buna N and dracon, convoluted  
1/4" NPT

---

Distributor:

4300 E / rev.00 05-2011