


Polyflo[®] quick connectors and hose

- *Easy connection*
- *Reliable operation*

Polyflo connectors and hose are used for connecting instruments under test to Tradinco pressure calibration and test equipment at pressures up to 10 barg.


The following models are available:



Female connector Model 266-P

Connections:


Left side : tubing
 Right side : female thread



Male connector Model 268-P

Connections:


Left side : tubing
 Right side : male thread



Body double end shut-off Model 294-PB

Connections:


Left side : tubing
 Right side : female/body



Insert without shut-off Model 294-PM

Connections:

Left side : insert/male/plug
 Right side : tubing



Body with shut-off Model 298-PT

Connections:

Left side : male thread
 Right side : female/body



Tubing:

Model 8635
 Model 44-P
 Model 66-P

Technical specifications

Ordering code	Description	Tube OD	Pipe thread (NPT)	Material	Finish	Dimensions		
						A	B	C
266-P-04 x 02	Female connector	1/4"	1/8"	Brass	-	25	19	12
266-P-04 x 04	Female connector	1/4"	1/8"	Brass	-	30	24	16
268-P-04 x 02	Male connector	1/4"	1/8"	Brass	-	26	20	11
268-P-04 x 04	Male connector	1/4"	1/4"	Brass	-	30	25	16
268-P-04 x 06	Male connector	1/4"	3/8"	Brass	-	32	26	17
268-P-06 x 04	Male connector	3/8"	1/4"	Brass	-	32	26	17
268-P-06 x 06	Male connector	3/8"	3/8"	Brass	-	32	26	17
294-PB 04	Body double end shut-off for panel mounting	1/4"	-	Brass	Chrome plated	45	-	16
294-PM 04	Insert	1/4"	-	Brass	Chrome plated	41	-	12
298-PT 04 x 02	Body with shut-off	1/4"	1/8"	Brass	Chrome plated	41	-	12
298-PT 04 x 04	Body with shut-off	1/4"	1/4"	Brass	Chrome plated	32	-	14
8635	Tubing*	1/4"	-	Polyurethane	-	-	-	-
44P-04	Tubing	1/4"	-	Nylon	-	-	-	-
66P-06	Tubing	3/8"	-	Nylon	-	-	-	-

* maximum 7 bar

Distributor: