


Polyflo[®] components

Polyflo connectors and hose are used for connecting instruments to be tested to Tradinco low pressure calibration and test equipments. Please also refer to our brochure "Polyflo[®] quick connectors and hose".


The following models are available:



Plastic sleeve Model 260-P




Universal nut and brass sleeve assembly Model 261-UB



Union tee Model 264-P

Connections:

All side : tubing




Male elbow Model 269-P

Connections:

Left side : tubing

Bottom : male thread




Female elbow Model 270-P

Connections:

Left side : tubing

Bottom : female thread




Male run tee Model 271-P

Connections:

Left side/bottom : tubing

Right side : male thread



Bulkhead union Model 282-P

For connections to:

Left side : tubing

Right side : tubing

Technical specifications

Ordering code	Description	Tube	Pipe thread (NPT)	Dimensions		
				A	B	C
260-P-04	Plastic sleeve	1/4"	-	8	-	-
260-P-04	Plastic sleeve	3/8"	-	9	-	-
261-UB-04	Universal nut and brass sleeve assembly	1/4"	-	9	-	11
264-P-04	Union tee	1/4"	-	21	16	10
264-P-06	Union tee	3/8"	-	23	17	12
269-P-04 x 02	Male elbow	1/4"	1/8"	21	16	10
269-P-04 x 04	Male elbow	1/4"	1/4"	22	17	10
269-P-06 x 04	Male elbow	3/8"	1/4"	25	18	12
270-P-04 x 02	Female elbow	1/4"	1/8"	23	16	10
271-P-06 x 04	Male run tee	3/8"	1/4"	23	17	12
282-P-04	Bulkhead union	1/4"	-	43	32	14

Distributor: