

## TRAQC 3 Series Temperature Calibrator

On the right TRAQC with the new Tradinco Quality Calibrators



Rugged

Lightweight

Easy to use in field

High benefit-cost ratio

High stability

Software

Modern design

**Tradinco Instruments B.V.**

Industrieweg 74 - P.O. Box 37  
2651 BD Berkel en Rodenrijs  
The Netherlands

Tel. +31 10 511 29 11

Fax +31 10 511 51 14

e-mail: [info@tradinco.com](mailto:info@tradinco.com)

website: [www.tradinco.com](http://www.tradinco.com)

TRAQC

# TRAQC 3 Series Temperature Calibrator

## Specifications:

Temperature range	Ambient +5°C to 375°C.
Resolution	0,1 °C/°F.
Accuracy	Over full range better than +/- 0,4 °C, typ. +/- 0.2°C
Stability	+/- 0,05 °C.
Heating time	Ambient to 300 °C 5.75 minutes.
Cooling time	300 °C to 60 °C 14 minutes.
Stabilization	5 minutes.
Well depth	Max 100 mm.
Switch test	Powerless switch, LED indicator, 5 VDC, 16 mA max.
Communication	RS232 for use with e.g. AutoCal
Supply voltage	220Volt, 50/60 Hz or 110 Volt, 50/60 Hz. Selectable.
Power consumption	250 Watts.
Fault protection	Internal sensor break detection.
Fuse	3.15 A .
Thermal Protection switch	75 °C
Temp switch test	5 VDC, 16 mA max.
Size	155 x 145 x 72.5 mm.
Safety	NEN –EN-IEC 601010.
Conformity (EC)	to NEN-EN-IEC 61000-4-3, -3-2, -3-3, -4-2, -4-4, -4-5

specifications may be changed without notice

