

TRAQC 3 Series Temperature Calibrator

On the right TRAQC with the new Tradinco Quality Calibrators



Rugged

Lightweight

Easy to use in field

High benefit-cost ratio

High stability

Software

Modern design

Tradinco Instruments B.V.

Industrieweg 74 - P.O. Box 37
2651 BD Berkel en Rodenrijs
The Netherlands

Tel. +31 10 511 29 11

Fax +31 10 511 51 14

e-mail: info@tradinco.com

website: www.tradinco.com

TRAQC

TRAQC 3 Series Temperature Calibrator

Specifications:

Temperature range	Ambient +5°C to 375°C
Resolution	0.1 °C/°F
Accuracy	Over full range better than +/- 0.4 °C, typ. +/- 0.2°C
Stability	+/- 0.05 °C
Heating time	Ambient to 300 °C in 5.75 minutes
Cooling time	300 °C to 60 °C in 14 minutes
Stabilization	5 minutes
Well dimensions	Depth 100 mm ; Diam 13 mm
Switch test	Powerless switch, LED indicator, 5 VDC, 16 mA max
Communication	RS232 for use with e.g. AutoCal
Supply voltage	220Volt, 50/60 Hz or 110 Volt, 50/60 Hz. Selectable
Power consumption	250 Watts
Fault protection	Internal sensor break detection
Fuse	3.15 A . (slow)
Thermal Protection switch	75 °C
Temp switch test	5 VDC, 16 mA max.
Safety	NEN –EN-IEC 601010
Conformity (EC)	to NEN-EN-IEC 61000-4-3, -3-2, -3-3, -4-2, -4-4, 4-5
Weight	approx. 1740 grams, without power cord, incl. 6.2 mm insert
Dimensions	w x d x h: 149 x 159 x 74 mm.

specifications may be changed without notice

